# 912GS RAIL



A compact rail ready **Dump Truck with great** features and performance, on or off rail.

### **Key features**

- 10 ton articulated dump truck
- Factory mounted rail wheel system
- MultiTip with 180° tipping range
- Easy switch between on and off rail
- Works in both high (Type 2a) and low (Type 3) rail





## Technical data.

### Construction

The standard version of the 912GS RAIL is mounted with af MultiTip body enabling the load to be tipped anywhere in a 180° range. The rail modules are bolted to the chassis and fitted with hydraulic quick couplings allowing the modules to be easily removed if and when the truck shall be used for standard earth moving duties.

### **Chassis**

Articulated chassis with center pivot, and two double acting hydraulic stabilizers. The stabilizers offers very high stability when driving and tipping. When on rails, the oscillation in the pivot point automatically lockes. The articulated steering is hydraulically locked from within the cab. The fueland hydraulic tanks are integrated in the front frame. Fuel tank: 140 L. AdBlue tank: 14L. Pivot oscillation +/- 12 °.

Hydrostatic load sensing pivot steering with two double acting cylinders, priority valve and integrated emergency steering. Steering cylinders with damping. Max, steering angle +/- 35°.

### **Hydraulic system**

Hydraulic pump with 84 L/min for tipping and steering. Priority valve for steering. Separate pump for brakes and stabilizers.

### 180° MultiTip

Compact swivel system, driven by two double acting cylinders. The system makes it possible to dump the load continuously over a 180° slew range. The robust system is mounted on a large slewing ball bearing.

The 912GS RAIL has electrohydraulic suspension, with two independent suspension cylinders on the front axle. The axles have planetary hub reduction, and separate oil reservoirs in the hubs. The front axle has an automatic limited slip differential lock, and the rear axle has a 100% electrohydraulic differential lock.

### **Brakes**

Dual circuit hydraulic servo system, with oil immersed brake discs at all 4 wheels. The brakes are self-adjusting and maintenance free. The parking brake is a maintenance free electrohydraulic fail-safe brake activating the brake discs in the front axle. On rail, the service- and parkingbrake works directly on the rail wheels.

### **Transmission**

Automatic ZF WG 115 ERGO POWER transmission, with 6 forward and 3 reverse gears. Electronic soft shift control system without traction interruption. Constant 4WD.

### **Engine**

Cummins B4.5 Stage 5 engine with DOC, DPF and SCR catalysts with AdBlue additive. 4.5 litre, 16 valve common rail turbo diesel with intercooler and electronically variable turbo charger.

Max power: 108 kW (147 hp) at 2000 rpm. Max. torque: 600 Nm at 1500 rpm.

### **Dumptruck body**

5,6 m<sup>3</sup> body robot-welded body in high tensile steel. Tipping angle 75°. Height stop at 4.3 m or 4.5 m as option.

### **Operator cab**

Spacious ROPS/FOPS approved cab with suspension and excellent view. Mechanical or air suspended seat. Adjustable steer-

### **Safety features**

Two cameras pointing directly at the rail wheels, help via displays in the cabin to lower them down on the track. A manual emergency pump is available for emergency operation.

Dimensions			
Tires: Michelin TrailXBib 600/55-26.5			
Unladen weight		kg	10.410
Load capacity		kg	10.000
Width over std. wheels		mm	2.470
Wheel base (road wheels)		mm	3.080
Length (rail wheels raised)		mm	6.330
Track (road wheels)		mm	1.860
Speed (road/rail)		km/h	35/20
High rail (Type 2a)			
Wheel base (rail wheels)		mm	4.980
Clearance height, cab		mm	3.020
Ground clearance (rails)		mm	125
Low rail (Type 3)			
Wheel base (rail wheels)		mm	5.240
Clearance height, cab		mm	2.820







